
# A SECURE WEB-BASED DIGITAL IMAGE LIBRARY

Mary Thompson, Srilekha Mudumbai, William Johnston

MRThompson@lbl.gov

http://imglib.lbl.gov



ERNEST ORLANDO LAWRENCE
BERKELEY NATIONAL LABORATORY



### General Image Library problem

#### Many large images

- hundreds to thousands
- 1 50 MBytes
- Associated textual metadata and derived images

# Images kept in centralized Mass Storage Systems or off-line storage

- on tape or removable disk- slow access
- remote from user slow network
- access methods awkward and restrictive



#### Images generated at remote sites

- medical images cardio-angiography, MRI, etc.
- electron microscopes

#### Image users at remote sites

collaborators at other sites



#### **Our Solution - A Web Server**

#### Solves two problems easily:

- user remote from the high-resolution images
- users at sites remote from each other sharing images

Server code is cgi scripts run by standard Web Server, e.g. NCSA HTTPD 4.1, Apache

Client code is standard Web browser, Netscape, MicroSoft Explorer



### Client/Server paradigm

SERVER (IMGLIB)

Has access to hi-res images

**Running HTTPD** 

Unix/Solaris

CLIENT (NETSCAPE)

Running any Web browser

PC/Mac/Unix

CLIENT (EXPLORER)

Running any Web browser

PC/Mac/Unix



#### **ImgLib Functional Overview**

**Cataloguing system** 

**Creates and manages Metadata** 

- creates and displays derived thumbnail images
- indexes and searches text information

Provides interface to tertiary storage

Does not modify original images



### **ImgLib Functions**

Smaller copy images are created and kept on-line on server machine

Collections are divided into logical hierarchical subcollections that are small enough to browse quickly with a Web browser


Provides a Web interface to get images from tertiary storage

Textual information about each image is stored and indexed to allow searching

All user or curator interactions are through Web




### **Browsing Interface**





### **Data Object Definition Document**





#### **Status**

#### Lung microscopy collection

- 1400 1-4 Megabyte scanning electron microscope images
- the primary researcher and his group members use ImgLib routinely to find and view his images

#### Lab Photo Archive

- 1000 images on-line selected from the thousands of photos in the Berkeley Lab archive
- they have been used for a variety of Web publications and for general browsing by people in and outside the Lab



#### Kaiser Permanente angiograms

- data collected daily for all patients from Oakland and Vallejo primary care centers (June '96 thru Jan'97)
- 2 weeks worth of data on a high-speed network memory cache (30 Gbytes) - 60 patient cardioangiography studies consisting of about 800 individual video clips stored
- 3 months of data on tertiary storage
- doctors at primary care institutions have used these images and are evaluating the project



### **Original Implementation**

#### **NCSA HTTPD server**

#### HTTPD cgi-scripts - Perl and C

- display dynamic index pages for a collection.
- display data-object definition documents
- fetch original image
- curating the collection



### Implementation (cont)

#### Public library packages

- glimpse search engine from Univ. of Arizona http://glimpse.cs.arizona.edu:1994/
- pbmplus image package, Jeff Poskanzer http://www.acme.com/software/
- cjpeg conversion Independent JPEG group ftp from ftp.uu.net/graphics/jpeg



#### **Access Control Limitations**

Web servers control GET and POST actions

Use local .htaccess files with user/password or domain access control.

Passwords are passed over the net uuencoded (not encrypted)

My scripts mimics this method, added additional .htaccess files to control write actions and access to original images.



### Requirements for Secure ImgLib

Data passed over the network must be encrypted Users wanting access must be securely identified Needs to work in a distributed collaborative environment

- Distributed stakeholders
- Distributed users
- Distributed access control

Want finer control over actions than just read and write



#### **Encrypted Network Connections**

#### Provided by Apache with SSL patches

- http://ww.apache.org
- ftp://ftp.psy.uq.oz.au/pub/Crypto/SSL
- ftp://ftp.ox.ac.uk/pub/crypto/SSL/ftp

#### Or buy a Netscape Web server

- FastTrack for \$295.

Use a server private key and certificate to encrypt the connections

Client needs to do nothing except reference https



# Securely Identify Users (Provided by Netscape)

Require users to get an Identity Certificate from a trusted CA

- Netscape CA \$525

Set server to require client authorization and tell it what CA's to trust.

Clients must now use Netscape Navigator and present their Identity Certificate with their requests. Navigator makes this straightforward.

Internet Explorer may use a different and incompatible method of handling Certificates.



#### **Distributed Access Control**

Distributed stakeholders create UseCondition certificates locally.

We provide a Java gui application that communicates with the resource server to help the stakeholder create a valid UseCondition and Attribute Certificates.

Certificates can be stored locally by the stakeholder but accessible via a Web or LDAP server or can be entered by the stakeholder into a central LDAP or Web Server.



### Image Lib Resources are Hierarchical

Collections are organized like directory trees.

Access control and curation tends to follow the same hierarchy.

The protection granularity for ImgLib is directories (aka collections of images).

We wish to be able to inherit access control from a parent directory as well as set it locally.



### ImgLib Resource Architecture

**Root Dir** 

**DieselCollabCA and Public Key** 

O=DieselCollab - allow access, read

O=LBNL - allow access

O=Sandia - allow access


**O=Cummins - allow access** 

**COLLECTIONS** - no authority file

**SCRIPTS** 

#### SANDIA

UCI=Mah/DCCA DN=Mah read,add modify,delete



#### **CUMMINS**

UCI- Smith/DCCA
OU=Cummins - read

**O=Cumins** 

text

DN=Brown/LBNL -read

DN=Smith -read, add modify, delete

images

#### **CATERPILLAR**

**UCI-Jones/DCCA** 

O=DieselCollab - read

DN=Jones -read,add modify,delete

text images



### **Authority Files**

Trusted starting point of access control

Files on the Server machine that can be associated with each resource to be protected

#### **Consists of:**

- places to look for certificates
- list of acceptable UseCondition issuers
- list of places to look for UseConditions



### **Root Authority File**

Must exist in the root of the resource tree

Contains the list of CA's to trust and their ID certificates (public key)

Places to find UseConditions

At least one UseCondition that grants the broadest allowed access to the resource tree. Otherwise we fail-safe and no-one is allowed access to the tree.



### ImgLib UseConditions

Name of the resource

Scope - local or sub-tree

Access and actions - read, add, delete, modify, fetch-hi-res

Conditional expression of attributes and values

Who can issue attribute certificates and their CA's

CA's to trust to verify the user identity

### Finding all the UseConditions


Given a request for a resource, Akenti has to know what Authority Files apply

We wish to be able to inherit access from a parent directory as well as set it locally

- Search resource directory for .htauthority file
- Check each parent directory for an .htauthority file.
- Use all the relevant UseConditions that are found.



### Making an access



### Akenti Policy Engine steps

#### Akenti Check Access interface called with:

- **DN** /C=US/O=DieselCollab/OU=LBNL/CN=Mary Thompson
- **RootDir** /opt/akenti/akenti-htdocs
- resourceDir COLLECTIONS/SANDIA
- authFileName .htauthority
- **protocolHost** https://www.diesel-colab.sandia.gov
- **allowedActions** returned (access,read,add,delete,modify,fetch-hi-res)



### Policy Engine steps (2)

# Policy Engine starts at resourceDir looking for Authority Files and works up to RootDirectory.

#### For each AuthFile it encounters:

- gathers up all the UseConditions
  - Does LDAP lookups
  - pulls through URLs
  - may search hash directories returned by URL.



### Policy Engine steps (3)

#### Builds a list of all relevant UseConditions

- Checks to see if the resource name in the UseCondition matches the resource we are referencing.
- Check that the scope includes the resource



### Policy Engine steps (4)

#### For each UseCondition that enables access:

- Checks the issuer and signature for validity
- If the user fails to satisfies any such UseCondition, he is denied access to the resource.

#### To see what actions are allowed:

- starts from the bottom up and finds the first directory that contained UseConditions.
- Checks all those UseConditions for validity.
- See which ones the user satisfies.
- Combines all the rights granted by these UseConditions.



#### **Status**

# Just starting deployment as part of the Diesel Combustion Collaboratory

#### To Do list

- Caching
  - Very short-term caching of permissions to a resource
  - Longer term caching of UseCondition and Attriubute certificates



#### To Do (cont)

- Vulnerability to network outage or insecure servers.
  - How to tell if UseConditions are not found
  - Use redundent distributed servers, and/or a reliable central server
  - Fail-safe or fail-soft?
- Allowing Authority Files to be managed remotely

